











D60

PC POS

Award-winning
exclusive design



-  **15,6 inch Display**
TFT true flat with high brightness.
-  **Slim and elegant profile**
with modern lines.
-  **LED backlight**
low consumption and long lasting.
-  **Chassis made of die-cast aluminum**
robust housing, water and dust resistant (IP65).
-  **Ergonomic flexible design**
enables interaction with the customer.
-  **Accessories**
A wide range of accessories for every need.
-  **Display 360°**
Tiltable and rotatable display allows maximum flexibility.
-  **Fanless cooling**
without moving parts and quiet (fanless).

TECHNICAL DETAILS

Pulse **D60** with its ergonomic design offers maximum flexibility. The tiltable and 360° rotatable display enables direct interaction with the customer.

The Pulse **D60** received the iF Design Award 2020 for its elegant design. The modern lines integrate perfectly into any sophisticated ambience.

The rich I/O ports with hidden cables and fanless design ensures Pulse **D60** to work perfectly in different scenarios.




Version		D60 J6412	D60 i3 (11th generation)
Processor		Intel® Elkhart Lake Celeron J6412	1 Intel® Tiger Lake i3-1115G4
RAM		8 GB RAM DDR4	8 GB RAM DDR4
System Memory (SSD)		128 GB SSD (M.2)	128 GB SSD (M.2)
LCD Screen	Size	15.6" FHD TFT Display	15.6" FHD TFT Display
	Resolution	1920 x 1080 pixel	1920 x 1080 pixel
	Touchscreen	True Flat PCAP Multi-touch	True Flat PCAP Multi-touch
External Interfaces front I/O	USB	1x USB2.0	1x USB2.0
	On/Off	front facing	front facing
External interfaces back I/O	USB	2x USB3.0 Type C, 2x USB3.0, 3x USB2.0	2x USB3.0 Type C, 2x USB3.0, 3x USB2.0
	Serial	2x DB9 (Powered RS232)(COM1 0V~/5V, COM2 0V~/12V)	2x DB9 (Powered RS232)(COM1 0V~/5V, COM2 0V~/12V)
	Ethernet	1x RJ45	1x RJ45
	Cash Drawer	1x RJ11	1x RJ11
	2 x FeDp	Power, transfer video and data with a single cable	Power, transfer video and data with a single cable
	DC Jack	1x 4PIN (with latch)	1x 4PIN (with latch)
Power Supply		90W / 19V	90W / 19V
Audio	Loud speaker	1x 2W	1x 2W
	Operating Temperature	0°C ~ 35°C	0°C ~ 35°C
Environment	Storage Temperature	-20°C ~ 60°C	-20°C ~ 60°C
	Humidity	20% ~ 85% RH non-condensing	20% ~ 85% RH non-condensing
	Certificate	FCC Class A, CE Mark, LVD	FCC Class A, CE Mark, LVD
OS Support		Windows IO IoT Enterprise, Linux	Windows IO IoT Enterprise, Linux
Size		369 x 200 x 375 mm	369 x 200 x 375 mm
Weight		5,4 kg	5,4 kg
Peripherals	MSR	3-Track MSR (USB)	3-Track MSR (USB)
	iButton	iButton (Dallas)	iButton (Dallas)
	WiFi und BT	M.2(E-Key)WiFi/BT Module	M.2(E-Key)WiFi/BT Module
	NFC	Yes	Yes
	Fingerprint	Yes	Yes
	Scanner	2D Scanner	2D Scanner
	LCM Customer Display	LCM Display 2x20 Zeichen	LCM Display 2x20 Zeichen
2nd Display	Touch and non-touch 10,1" and 15,6"	Touch and non-touch 10,1" and 15,6"	

Care Gold guarantee 24 months (extendable up to 6 years)

OPTIONAL ACCESSORIES



NFC



iButton
(Dallas)



Fingerabdruck



MSR



Scanner